

Nexthop NH-4000 Series Introduction

The NH-4000 series is a family of high density 800 GbE, fixed form factor, air-cooled, 51.2 Tbps switches, purpose built for modern cloud and AI data centers for front-end or back-end scale-out or scale-across use cases. The family provides 51.2 Tbps of switching capacity, powered by flexible SerDes technology that enables various port configurations for 800 GbE, 400 GbE, 200 GbE or 100 GbE applications. Additionally, the switch offers sophisticated packet processing, buffering, traffic management, congestion control, queuing and telemetry capabilities. As a result, the NH-4000 family of switches is ideally suited for advanced AI back-end and front-end networks in leaf, spine, middle-of-row, and end-of-row configurations.



Technical Capabilities and Features

The NH-4000 series is optimized to handle the extreme demands of advanced AI back-end and front-end networks by incorporating specialized capabilities essential for high-performance computing. This includes RoCEv2 and DCQCN (Priority Flow Control and Explicit Congestion Notification) for ensuring low-latency data transport, combined with Dynamic Load Balancing (DLB) and high radix ECMP for efficient traffic distribution across the network and advanced Telemetry and Monitoring for troubleshooting and traffic visibility.

Performance Highlights

- 51.2 Tbps Line-Rate Switching
- Advanced IPv4/IPv6 Packet Processing.
- Hardware-based Encapsulations and Tunneling
- Sophisticated On-Chip Buffering and Traffic Management

Advanced AI Features

- AI Optimized: RoCEv2 and DCQCN
- Dynamic Load Balancing (DLB)
- High Radix ECMP

The **NH-4010-F platform** delivers 64 ports of 800G in a 2RU system with a throughput of 51.2 Tbps. The platform also has 2 dedicated SFP+ front panel ports.



64 x 800GbE OSFP
+ 2 x 10/25GbE SFP



Front-to-Back Airflow
Redundant PSU and Fans

NH-4010-F Platform Specifications

Model Number	SKU	NH-4010-F
CPU	Processor	AMD Ryzen Embedded V3000, 8 core/16 thread; 64-bit x86
	Memory	32 GB DDR5-4800
	Security	Infineon SLB 9672 TPM 2.0
	Boot Storage	32 MB SPI
	BMC	N/A
	Storage	240 GB, M.2 2280, NVMe SSD
Form Factor	Rack Units	2 RU, EIA-310 rack or equivalent type
	Dimensions (H x W x D)	3.48" x 17.3" x 23.6" 89 mm x 440 mm x 600 mm
	Weight	49.8 lbs (22.59 kg) - with modules
Hardware	Power Supply	Hot swappable, 2 (1+1) redundant, 2400 W, AC
	Fan	Hot swappable, 4 (3+1) redundant
	Cooling	Front-to-back airflow
Ports	Network	64 x 800 GbE OSFP, 2 x 10/25 GbE SFP28
	Management	1 x 10/100/1000BASE-T RJ45
	USB	1 x USB 2.0 Type-C

	Console	1 x RJ45 serial console port
System Power	AC Input Typical Power DAC ¹ Typical Power Optics ² Maximum Power ³	200-240 VAC, 50 - 60 Hz 584 W 1591 W 2038 W
Operating Conditions	Temperature Humidity Altitude	0°C to 40°C / 32°F to 104°F 5% to 90% (RH), non-condensing 0 to 10,000 ft (0 – 3000 m)
Non Operating Conditions	Temperature Humidity	-40°C to 70°C / -40°F to 158°F 5% to 95% (RH), non-condensing

¹ 800 GbE, L3, Large frames, Random payload, 25°C, 50% traffic load, DAC
² 800 GbE, L3, Large frames, Random payload, 25°C, 50% traffic load, FRO
³ 800 GbE, L3, Large frames, Random payload, 45°C, 100% traffic load, FRO

Switch Silicon Specifications

Network Scaling⁴	SerDes Technology	100Gbps PAM4, 512 SerDes
	Flexible Port configs	Up to 64 ports 800 GbE Up to 128 ports of 400 GbE Up to 256 ports of 200 GbE Up to 320 ports of 100 GbE Up to 320 ports of 50 GbE
	Dynamic Buffer	165 MB unified packet buffer (Static & Dynamic Buffer Allocation)
	MAC Addresses	128K
	VLANs	4K
	ACLs	3K
	Egress ACLs	512
	ECMP	128-way Next hop groups: 4K, 128K members
	IPv4 Routes	850K
	IPv6 Routes	600K
	IPv4 Multicast (S,G)	128K
Key Features	Queuing and scheduling	Up to 12 queues per port and a variety of scheduling algorithms (SP, RR, WRR, WDRR)
	QoS features	DSCP, Hierarchical ECMP, rate limiting, and shaping
	Advanced AI	ROCEv2, DCQCN (PFC, ECN), DLB, high-radix ECMP
	Telemetry and Monitoring	Port Mirroring, Flow Mirroring, ERSPAN (ingress and egress), Mirror on Drop (MoD), In-band Telemetry (INT)

⁴ Software-supported features and scale numbers depend on the NOS and the software version.

Software Support

The NH-4000 series switches come preinstalled with the Open Networking Install Environment (ONIE) bootloader.

The NH-4000 series switches support multiple network operating systems including community Software for Open Networking in the Cloud (SONiC) as well as Nexthop NOS.

For software release version support, checkout the [SW Release page](#) or contact support@nexthop.ai.

Regulatory Compliance

Safety	UL/CSA 62368-1:2019, IEC 62368-1:2018
EMC	FCC part 15, Class A ICES-003 VCCI-CISPR 32 AS/NZS CISPR 32 EN 55032 BS EN55032 CISPR 32 KS C 9832 CNS 15936 EN 55035 BS EN55035 CISPR 35 EN 61000-3-2 IEC 61000-3-2 BS EN IEC 61000-3-2 EN 61000-3-3 IEC 61000-3-3 BS EN 61000-3-3 KS C 9835
Certifications	BSMI (Taiwan) CE (European Union) KCC (South Korea) NRTL (North America) RCM (Australia/New Zealand) VCCI (Japan)
EU Directives	2014/35/EU Low Voltage Directive 2014/30/EU EMC Directive 2012/19/EU WEEE Directive 2011/65/EU RoHS Directive 2015/863/EU Commission Delegated Directive

Ordering Information

SKU	Product Description
NH-4010-F	64 port 800GbE OSFP, 51.2 Tbps, 2RU scale-out switch platform with front to back air flow, redundant, hot swappable power supplies (1+1) and fans (3+1)
PSU-AC-2400	AC Power Supply Unit, 2.4 KW, Hot swappable, CRPS-185 form factor
FAN-12V80G1-F	Dual Rotor Fan Module, front to back air flow, 80mm
NH-CHS-4010	Field replaceable unit for 64 port 800GbE OSFP, 51.2 Tbps, 2RU scale-out switch platform
NH-SVC-4010-NBD	24x7 Nexthop TAC and next business day RMA support for the NH-4010-F platform

Ready to Get Started?

To learn more about the NH-4000 Series of switches including technical specifications and user guide, refer to the [Nexthop platforms page](#).

© 2026 Nexthop Systems Inc. All rights reserved. nexthop ai, the nexthop ai logo, and all related product and software names are trademarks of Nexthop Systems Inc. All other trademarks or service marks are the property of their respective owners. Product specifications and information are subject to change without notice.